

Model	Speed flex high speedfold-up door.
Wind Resistance (EN-13241-1+ A1)	Class 1
Structural Load (ASTM D 638/790)	0.4 kN/m ²
Structure	Aluminum (T 6063-T6)
Intermediate beams	Aluminum (T 6063-T6)
Bottom beam	Aluminum (T 6063-T6)
Drum	Aluminum (No Welding process)
Side Guide	Aluminum
Thickness of Door Structure	20 mm-double skin filled with xps material
Water Tightness (EN 13241-1+A1)	Class2
Air Permability(EN 13241-1+A1)	Class2
U Value (BS EN ISO 6946)	0.8 W/m ² k
Insulation material	Xps (Flame retardant)
Sound attenuation	14 dBA
Avalible height	4 mt
Avalible width	5 mt
Working Speed	1.2 mt/sec opening 0.8 mt/sec closing
Motor	1 pieces
Motor Power	1.5-2.2 Kw
Operation temperature	-35 [°] c + 70 [°] c
Bottom Safety Edge	Optional
Heater	30 W silicone cable heater(Optional)
Safety Photocell	Standard
Emergency Opening	Crank Manuel (counter balance –optional)
Side Insulation	Standard
Bottom Insulation	Standard
Coating	Anodising Aluminium
SF Safety factor	>6